

# HOW TO ORDER

The categories shown on this key are provided to cover standard features of **SWITCHLINK®**. Please use these figure numbers to ensure prompt and accurate processing of your order. A detailed description must accompany any special orders.

**SWITCHLINK®**      **A**      **B**      **C**  
             

*Example:*      **A**      **B**      **C**  
 I       0  7  2       W  L  1

**A** *Model Number*  
**I** Maximum Recommended torque 1250 in-#  
 2-4" Flanged Ball Valve  
 3-4" Threaded Ball Valve  
 1 ½ -2" Plug Valve

**II** Maximum Recommended torque 500 in-#  
 Up to 1 ½" Flanged Ball Valve  
 Up to 2" Threaded Ball Valve  
 Up to 1" Plug Valve

**B** *Standard Bottom Configurations*  
 Model I

- KS1** -3 ¼ " B.C. with 3/8-16 tapped holes  
 Drive: 1 1/8" Dia. with ¼" Sq. Key
- KS2** -5" B.C. with ½ -13 tapped holes, 1 ¼ " Stem Ht.  
 Drive: 1 1/8" Dia. with ¼" Sq. Key
- KS3** -5" B.C. with ½ -13 tapped holes, 2" Stem Ht  
 Drive: 1 1/8" Dia. with ¼" Sq. Key
- 071** -70mm B.C. with 5/16-18 tapped holes  
 Drive: 1 1/8" Dia. with ¼" Sq. Key
- 072** -70mm B.C. with 5/16-18 tapped holes  
 Drive: 19mm sq.
- 073** -70mm B.C. with 5/16-18 tapped holes  
 Drive: 17 mm sq.

Model II

- F05** -50mm B.C. with ¼-20 tapped holes  
 Drive: 14 mm sq.

## **C** *Standard Top Configurations*

<b>WL1</b> Westlock Standard Mount	<b>AJ1</b> ASCO Standard Mount
<b>WL2</b> Westlock Namur Mounting	<b>AJ2</b> ASCO Namur Mount
<b>WLB</b> Westlock Beacon	<b>AJ3</b> ASCO Pointer
<b>AC1</b> Accord Standard Mount	<b>GO1</b> Go Switch Model 41 Std.
<b>AC2</b> Accord Namur Mount	<b>GO2</b> Go Switch Model 41 Namur
<b>ST1</b> Stonel Onyx	<b>KS1</b> Keystone Namur Mount
<b>ST2</b> Stonel Quartz	<b>PX1</b>
<b>AX1</b> Automax Standard Mount	<b>MN1</b> Moniteur
<b>AX2</b> Automax Namur Mount	<b>WO1</b> Worcester Mas
<b>BR1</b> Bray Series 50	<b>NA1</b> 80 X 20mm Namur Std.
<b>BR2</b> Bray Series 52	<b>EF1</b> Effector IND Switch w/17105 puck
<b>SV 1</b> Save Vision Namur	

## **ACCESSORIES**



1. Mounting kits for use with non direct mounting valves.
2. Lockouts
3. Ten position function
4. Clean service/ wash down addition:
5. Handle Extensions



**CALL FOR PRICING, ORDERING INFORMATION,  
AND YOUR SPECIAL REQUIREMENTS**